



UT60 SERIES

Digital Multimeters



UT60BT

UT60BT digital multimeter has a built-in Bluetooth module which can be used with iDMM2.0 app.



- Smart phone APP: iDMM2.0
- Works with UT-D07B Bluetooth adaptor
- Download from App Store or Google Play



UT60EU

Specification	Range	UT60EU	UT60BT
DC voltage (V)	1000V	$\pm(0.5\%+3)$	
AC voltage (V)	1000V	$\pm(0.8\%+3)$	
DC current (A)	10A	$\pm(0.8\%+3)$	
AC current (A)	10A	$\pm(1.0\%+3)$	
Resistance (Ω)	100M Ω	$\pm(0.8\%+2)$	
Capacitor (F)	10mF	$\pm(4.0\%+5)$	
Frequency (Hz)	99.99Hz~9.999MHz	$\pm(0.1\%+5)$	
Duty cycle (%)	0.1~99.9%	$\pm(3\%+5)$	
Temperature ($^{\circ}\text{C}/^{\circ}\text{F}$)	-40 $^{\circ}\text{C}$ ~1000 $^{\circ}\text{C}$ /-40 $^{\circ}\text{F}$ ~1832 $^{\circ}\text{F}$	$\pm 4^{\circ}\text{C}/\pm 5^{\circ}\text{F}$	

Features

Bluetooth	UT60BT only
Display count	9999
Auto range	✓
REL	✓
NCV	✓
Diode	✓
Continuity test	✓
Acousto-optic indication (NCV/continuity/battery power)	✓
Low battery indication	$\leq 3.6\text{V}$
Data hold	✓
Auto power off	15Min
Operating temperature	0 $^{\circ}\text{C}$ ~40 $^{\circ}\text{C}$
Overvoltage category	CATII 1000V/CATIII 600V

Characteristics

Battery	1.5V AAA x3
Product color	Red and gray
Product net weight	290g
Product size	169 x 81 x 45mm
Standard individual packing	Gift box, manual, thermocouple
Standard quantity per carton	20pcs
Standard carton size	420 x 320 x 300mm