







LT-20 Series

 LT-422		 LT2-8	
 LT-623		 LT4-8	
 LT-633		 LT3-12	
 LT-933		0.4~2.5mm² 0.5~4mm² 250V/4kV/32A 	

TECHNICAL PARAMETER

Model	LT-422	LT-623	LT-633	LT-933	LT2-8	LT4-8	LT3-12
Appearance Specification							
Reference standard	IEC	IEC	IEC	IEC	IEC	IEC	IEC
Rated voltage	250V	250V	250V	250V	250V	250V	250V
Rated current	32A	32A	32A	32A	32A	32A	32A
Wired iameter	0.5~4mm ²	0.5~4mm ²	0.5~4mm ²	0.5~4mm ²	0.5~4mm ²	0.5~4mm ²	0.5~4mm ²
Voltage resistance	4kV	4kV	4kV	4kV	4kV	4kV	4kV
Mechanical properties							
Ambient temperature	-40°C~+105°C	-40°C~+105°C	-40°C~+105°C	-40°C~+105°C	-40°C~+105°C	-40°C~+105°C	-40°C~+105°C
Strip length	11-12mm	11-12mm	11-12mm	11-12mm	11-12mm	11-12mm	11-12mm
L/W/H	39.3×23.3×14.4	39.3×33.3×14.4	39.3×33.3×14.4	39.3×48.3×14.4	39.3×43.3×15.4	39.3×43.3×15.4	39.3×63.3×15.4
The number of poles	2P	2P	3P	3P	2P	4P	3P
Lever colour							
Plastic parts	PC,UL94,V-2	PC,UL94,V-2	PC,UL94,V-2	PC,UL94,V-2	PC,UL94,V-2	PC,UL94,V-2	PC,UL94,V-2
Shrapnel	S301	S301	S301	S301	S301	S301	S301
Conductor material	T2	T2	T2	T2	T2	T2	T2

First Step
Strip the wire 11-12mm

Second Step
Dismantle the orange operation handle straight and plug the wire into the hole.

Third Step
Push the lever horizontally to clip the wire for brake.