

BUS BAR PROCESSOR

JG-DHY-150 / JG-DHY-200

With three functions (cutting, punching and bending)



JG-DHY-150

M.R.P.

₹ 700000/-

JG-DHY-200

M.R.P.

₹ 750000/-

- 3 in 1 bus bar processor for cutting, punching and bending of copper bus bar and aluminum bus bar
- It is designed for irregular sized bus bar procession on Mid small scaled transformer, switchboard bor line or assembling site .
- Punch holes without burr. Cutting surface smooth and cutting angle accurately. It's good for quick and repeat batch procession.
- Four war valve control switch accurately guide to the position of punching, bening and cutting.
- Safe and firm pedal switch could control oil inlet and oil return

	JG-DHY-150	JG-DHY-200
Voltage	single phase 50Hz,220V	single phase 50Hz,220V
Rating pressure	700kg/cm ²	700kg/cm ²
Cutting force	20T	30T
Cutting range	150mm(W) × 10mm(T)	200mm(W) × 10mm(T)
Punching force	30T	35T
Distance from hole to sheet side	95mm	95mm



MAP10-4

Hole Diameter: 2 1/2" (76.1), 3" (88.9), 3 1/2" (102.9), 4" (115.5)



MAP10-4	2 1/2" (76.1), 3" (88.9)
Hole Diameter	3 1/2" (102.9), 4" (115.5)

MS46x46	1-13/16" (46.0 × 46.0)
MS50.8x50.8	2" (50.8 × 50.8)
MS68x68	2-11/16" (68.0 × 68.0)
MS92x92	3-5/8" (92.0 × 92.0)
MS104.8x104.8	4-1/8" (104.8 × 104.8)

	GROUP F
F1	32 × 32mm
F2	46.5 × 46.5 mm
F3	76.5 × 76.5 mm
F4	80.5 × 80.5 mm
F5	90.5 × 90.5 mm
F6	113 × 113mm
F7	151 × 151 mm

Special size of dies can de made by us based on big quantity

