

TB 10 EI BU - Feed-through terminal block



3246748

<https://www.phoenixcontact.com/in/products/3246748>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 1000 V, nominal current: 57 A, number of connections: 2, number of positions: 1, connection method: Screw connection, Rated cross section: 10 mm², cross section: 1.5 mm² - 16 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: blue

Commercial data

Item number	3246748
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE1
Product key	BEK211
GTIN	4046356605649
Weight per piece (including packing)	15.413 g
Weight per piece (excluding packing)	15.413 g
Customs tariff number	85369010
Country of origin	IN

TB 10 EI BU - Feed-through terminal block



3246748

<https://www.phoenixcontact.com/in/products/3246748>

Technical data

Product properties

Product type	Feed-through terminal block
Number of positions	1
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	2.43 W

Connection data

Number of connections per level	2
Nominal cross section	10 mm ²
Screw thread	M4
Tightening torque	1.2 ... 1.4 Nm
Stripping length	10 mm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	1.5 mm ² ... 16 mm ²
Cross section AWG	14 ... 6 (converted acc. to IEC)
Conductor cross section flexible	1.5 mm ² ... 10 mm ²
Conductor cross section, flexible [AWG]	14 ... 8 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	1.5 mm ² ... 10 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	1.5 mm ² ... 6 mm ²
2 conductors with same cross section, solid	1.5 mm ² ... 4 mm ²
2 conductors with the same cross-section AWG rigid	16 ... 12 (converted acc. to IEC)
2 conductors with same cross section, flexible	1.5 mm ² ... 4 mm ²
2 conductors with the same cross-section AWG flexible	16 ... 12 (converted acc. to IEC)
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	1.5 mm ² ... 2.5 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	1.5 mm ² ... 2.5 mm ²
Nominal current	57 A
Maximum load current	57 A (with 16 mm ² conductor cross section)
Nominal voltage	1000 V (in the case of enclosed clamping space)
Nominal cross section	10 mm ²

Dimensions

Width	10.2 mm
-------	---------

TB 10 EI BU - Feed-through terminal block



3246748

<https://www.phoenixcontact.com/in/products/3246748>

End cover width	1.8 mm
Height	42.8 mm
Depth on NS 32	52.8 mm
Depth on NS 35/7,5	47 mm
Depth on NS 35/15	54.5 mm

Material specifications

Color	blue
Flammability rating according to UL 94	V2
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Test voltage setpoint	9.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 10 mm ²	1.2 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	2.2 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

TB 10 EI BU - Feed-through terminal block



3246748

<https://www.phoenixcontact.com/in/products/3246748>

Attachment on the carrier

Result	Test passed
--------	-------------

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	1.5 mm ² / 0.4 kg
	10 mm ² / 2 kg
	16 mm ² / 2.9 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2018-05
Spectrum	Service life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	6.12 (m/s ²) ² /Hz
Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

TB 10 EI BU - Feed-through terminal block



3246748

<https://www.phoenixcontact.com/in/products/3246748>

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

TB 10 EI BU - Feed-through terminal block

3246748

<https://www.phoenixcontact.com/in/products/3246748>



Drawings

Circuit diagram



TB 10 EI BU - Feed-through terminal block



3246748

<https://www.phoenixcontact.com/in/products/3246748>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/3246748>

 UL Recognized Approval ID: E60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B	600 V	50 A	16 - 6	-
Use group C	600 V	50 A	16 - 6	-
Use group F	600 V	50 A	16 - 6	-
Use group D	600 V	5 A	16 - 6	-

TB 10 EI BU - Feed-through terminal block



3246748

<https://www.phoenixcontact.com/in/products/3246748>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

ETIM

ETIM 8.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121410
-------------	----------

TB 10 EI BU - Feed-through terminal block



3246748

<https://www.phoenixcontact.com/in/products/3246748>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

TB 10 EI BU - Feed-through terminal block



3246748

<https://www.phoenixcontact.com/in/products/3246748>

Accessories

INB 10-10 - Insertion bridge

3246201

<https://www.phoenixcontact.com/in/products/3246201>

Insertion bridge, pitch: 10 mm, number of positions: 10, color: gray



D-TB 4/10 E - End cover

3246104

<https://www.phoenixcontact.com/in/products/3246104>

End cover, depth: 35.9 mm, width: 1.5 mm, height: 42.5 mm, color: dark gray



TB 10 EI BU - Feed-through terminal block



3246748

<https://www.phoenixcontact.com/in/products/3246748>

TS-TB - Separating plate

3062838

<https://www.phoenixcontact.com/in/products/3062838>



Separating plate, for electrical isolation of neighboring bridges in the terminal center, depth: 22 mm, height: 22 mm, color: dark gray

ATP-TB - Partition plate

3046272

<https://www.phoenixcontact.com/in/products/3046272>



Partition plate, depth: 45.7 mm, width: 3 mm, height: 56 mm, color: dark gray

TB 10 EI BU - Feed-through terminal block

3246748

<https://www.phoenixcontact.com/in/products/3246748>



NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/in/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/in/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

TB 10 EI BU - Feed-through terminal block

3246748

<https://www.phoenixcontact.com/in/products/3246748>



PS-MT - Test plug

0311647

<https://www.phoenixcontact.com/in/products/0311647>

Test plug, number of positions: 1, color: silver



PS-IH WH - Insulating sleeve

0311566

<https://www.phoenixcontact.com/in/products/0311566>

Insulating sleeve, number of positions: 1, color: white



TB 10 EI BU - Feed-through terminal block

3246748

<https://www.phoenixcontact.com/in/products/3246748>



PS-IH RD - Insulating sleeve

0311579

<https://www.phoenixcontact.com/in/products/0311579>

Insulating sleeve, number of positions: 1, color: red



PS-IH BU - Insulating sleeve

0311582

<https://www.phoenixcontact.com/in/products/0311582>

Insulating sleeve, number of positions: 1, color: blue



TB 10 EI BU - Feed-through terminal block

3246748

<https://www.phoenixcontact.com/in/products/3246748>



PS-IH YE - Insulating sleeve

0311595

<https://www.phoenixcontact.com/in/products/0311595>

Insulating sleeve, number of positions: 1, color: yellow



PS-IH GN - Insulating sleeve

0311605

<https://www.phoenixcontact.com/in/products/0311605>

Insulating sleeve, number of positions: 1, color: green



TB 10 EI BU - Feed-through terminal block

3246748

<https://www.phoenixcontact.com/in/products/3246748>



PS-IH GY - Insulating sleeve

0311621

<https://www.phoenixcontact.com/in/products/0311621>

Insulating sleeve, number of positions: 1, color: gray



PS-IH BK - Insulating sleeve

0311634

<https://www.phoenixcontact.com/in/products/0311634>

Insulating sleeve, number of positions: 1, color: black



TB 10 EI BU - Feed-through terminal block

3246748

<https://www.phoenixcontact.com/in/products/3246748>



PS-IH VT - Insulating sleeve

0311618

<https://www.phoenixcontact.com/in/products/0311618>



Insulating sleeve, number of positions: 1, color: violet

SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/in/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

TB 10 EI BU - Feed-through terminal block

3246748

<https://www.phoenixcontact.com/in/products/3246748>



E/TB - End bracket

3246966

<https://www.phoenixcontact.com/in/products/3246966>

End clamp, for assembly on NS 32 or NS 35/7.5 DIN rail



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in