

TB 16 EI GN - Feed-through terminal block



3214153

<https://www.phoenixcontact.com/in/products/3214153>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 1000 V, nominal current: 76 A, number of connections: 2, connection method: Screw connection, Rated cross section: 16 mm², cross section: 6 mm² - 16 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: green

Commercial data

Item number	3214153
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE1
Product key	BEK211
GTIN	4046356905176
Weight per piece (including packing)	99.99 g
Weight per piece (excluding packing)	99.99 g
Customs tariff number	85369010
Country of origin	IN

TB 16 EI GN - Feed-through terminal block



3214153

<https://www.phoenixcontact.com/in/products/3214153>

Technical data

Product properties

Product type	Feed-through terminal block
Number of connections	2
Number of rows	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
---------------------	------

Connection data

Number of connections per level	2
Nominal cross section	16 mm ²
Screw thread	M4
Tightening torque	2.5 ... 3 Nm
Stripping length	12 mm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	6 mm ² ... 16 mm ²
Cross section AWG	8 ... 6 (converted acc. to IEC)
Conductor cross section flexible	6 mm ² ... 16 mm ²
Conductor cross section, flexible [AWG]	8 ... 6 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	6 mm ² ... 16 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	6 mm ² ... 16 mm ²
Cross-section with insertion bridge, rigid	16 mm ²
Cross-section with insertion bridge, flexible	16 mm ²
2 conductors with same cross section, solid	4 mm ² ... 10 mm ²
2 conductors with same cross section, flexible	4 mm ² ... 10 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	4 mm ² ... 6 mm ²
Nominal current	76 A
Maximum load current	76 A
Nominal voltage	1000 V
Note	Checked at 1100 V
Nominal cross section	16 mm ²

Dimensions

Width	12.2 mm
End cover width	1.5 mm
Height	51 mm
Depth on NS 32	55.5 mm

TB 16 EI GN - Feed-through terminal block



3214153

<https://www.phoenixcontact.com/in/products/3214153>

Depth on NS 35/7,5	50.5 mm
Depth on NS 35/15	58 mm

Material specifications

Color	green
Flammability rating according to UL 94	V2
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-40 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

TB 16 EI GN - Feed-through terminal block

3214153

<https://www.phoenixcontact.com/in/products/3214153>



Drawings

Circuit diagram



TB 16 EI GN - Feed-through terminal block



3214153

<https://www.phoenixcontact.com/in/products/3214153>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/3214153>



EAC
Approval ID: RU C-DE.A*30.B.01742

 UL Recognized Approval ID: E60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B				
	600 V	76 A	10 - 4	-
Use group C				
	600 V	76 A	10 - 4	-

TB 16 EI GN - Feed-through terminal block



3214153

<https://www.phoenixcontact.com/in/products/3214153>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

TB 16 EI GN - Feed-through terminal block



3214153

<https://www.phoenixcontact.com/in/products/3214153>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

TB 16 EI GN - Feed-through terminal block



3214153

<https://www.phoenixcontact.com/in/products/3214153>

Accessories

SCBI 10-12 - Screw bridge

3246159

<https://www.phoenixcontact.com/in/products/3246159>

Screw bridge, with insulating collar, number of positions: 10, color: silver



INB 10-12 - Insertion bridge

3246214

<https://www.phoenixcontact.com/in/products/3246214>

Insertion bridge, Bridging in the terminal point, pitch: 12 mm, number of positions: 10, color: gray



TB 16 EI GN - Feed-through terminal block



3214153

<https://www.phoenixcontact.com/in/products/3214153>

D-TB 16 E - End cover

5793004

<https://www.phoenixcontact.com/in/products/5793004>

End cover, depth: 42.8 mm, width: 2.2 mm, height: 50 mm, color: dark gray



TPS 4/7/6 - Test plug strip

3246243

<https://www.phoenixcontact.com/in/products/3246243>

Test plug strip, for 4 mm test plugs, for screwing into the bridge shaft, number of positions: 1, color: silver



TB 16 EI GN - Feed-through terminal block

3214153

<https://www.phoenixcontact.com/in/products/3214153>



SZS 1,0X6,5 VDE - Screwdriver

1205079

<https://www.phoenixcontact.com/in/products/1205079>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 6.5 x 150 mm, 2-component grip, with non-slip grip

E/TB - End bracket

3246966

<https://www.phoenixcontact.com/in/products/3246966>



End clamp, for assembly on NS 32 or NS 35/7.5 DIN rail

TB 16 EI GN - Feed-through terminal block

3214153

<https://www.phoenixcontact.com/in/products/3214153>



NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/in/products/1201002>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/in/products/1201015>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver

TB 16 EI GN - Feed-through terminal block

3214153

<https://www.phoenixcontact.com/in/products/3214153>



PS-MT - Test plug

0311647

<https://www.phoenixcontact.com/in/products/0311647>

Test plug, number of positions: 1, color: silver



PS-IH WH - Insulating sleeve

0311566

<https://www.phoenixcontact.com/in/products/0311566>

Insulating sleeve, number of positions: 1, color: white



TB 16 EI GN - Feed-through terminal block

3214153

<https://www.phoenixcontact.com/in/products/3214153>



PS-IH RD - Insulating sleeve

0311579

<https://www.phoenixcontact.com/in/products/0311579>

Insulating sleeve, number of positions: 1, color: red



PS-IH BU - Insulating sleeve

0311582

<https://www.phoenixcontact.com/in/products/0311582>

Insulating sleeve, number of positions: 1, color: blue



TB 16 EI GN - Feed-through terminal block



3214153

<https://www.phoenixcontact.com/in/products/3214153>

PS-IH YE - Insulating sleeve

0311595

<https://www.phoenixcontact.com/in/products/0311595>

Insulating sleeve, number of positions: 1, color: yellow



PS-IH GN - Insulating sleeve

0311605

<https://www.phoenixcontact.com/in/products/0311605>

Insulating sleeve, number of positions: 1, color: green



TB 16 EI GN - Feed-through terminal block

3214153

<https://www.phoenixcontact.com/in/products/3214153>



PS-IH GY - Insulating sleeve

0311621

<https://www.phoenixcontact.com/in/products/0311621>

Insulating sleeve, number of positions: 1, color: gray



PS-IH BK - Insulating sleeve

0311634

<https://www.phoenixcontact.com/in/products/0311634>

Insulating sleeve, number of positions: 1, color: black



TB 16 EI GN - Feed-through terminal block

3214153

<https://www.phoenixcontact.com/in/products/3214153>



PS-IH VT - Insulating sleeve

0311618

<https://www.phoenixcontact.com/in/products/0311618>

Insulating sleeve, number of positions: 1, color: violet



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in