

HYDRAULIC CRIMPING TOOLS

JG-YQK-70

- Hexagonal mould is adopted to ensure tight press connection, good electric conduction and non-easy shedding.



M.R.P.

₹ 7500/-

Range of application	6-70mm ²
Crimping force	6ton
Stroke	10mm
Standard	8-38, 60-70mm ² , : 14-22, 38-60, 70mm ²
Weight	2.5Kg
Packaging size	545x130x235mm
Package	Plastic case

JG-YQK-400

- Hexagonal mould is adopted to ensure tight press connection, good electric conduction and non-easy shedding.



M.R.P.

₹ 12000/-

Range of application	16-400mm ²
Crimping force	16T
Crimping type	Hexagon Crimping
Stroke	20mm
Length	approx 500mm
Weight	approx 6.80 kg
Package	Steel Case
Weight of Case	approx. 3.30 kg
Crimping Dies	16,25,35,50,70,95,120,150,185,240,300, 400 mm ²

JG-YQK-300A

- Hexagonal mould is adopted to ensure tight press connection, good electric conduction and non-easy shedding.



M.R.P.

₹ 7500/-

Range of application	10-185mm ² (Al Terminal) 16-300mm ² (Cu Terminal)
Crimping force	8ton
Stroke	16mm
Standard	16,25,35,50,70,95,120,150,185,240,300mm ²
Weight	6.4Kg
Packaging size	755x130x230mm
Package	Plastic case

JG-KYQ-400



M.R.P.

₹ 17500/-

Range of application	50-400 mm ²
Crimping force	16T
Crimping type	Hexagon Crimping
Stroke	20mm
Length	approx 500mm
Weight	approx 6.80 kg
Package	Steel Case
Weight of Case	approx. 3.30 kg
Crimping Dies	50,70,95,120,150,185,240,300,400 mm